FDK-10000LE

Portable Generators

GENERAL SPECIFICATIONS

Engine Model	195F
Standby (kVA)	9.4 kVA
Standby (kW)	7.5 kW
Prime (kVA)	6.8 / 8.5 kVA
Continuous Output Current (Ampere)	29.6

1 Standby power: Used as a backup to mains power, as an emergency power source under variable load, no overloading.
2 Prime Power: Continuous power source under variable load for 24/24 hours. 1/12 hour 10% overloading is permitted.

TECHNICAL SPECIFICATIONS

Maximum Power (kW/kVA)	7.5 / 9.4
Continuous Power (kW/kVA)	6.8 / 8.5
Number of phases	1 (Single-phase)
Output Voltage	230 Volt
Frequency	50 Hertz
Display	Dijital
Cylinders / Cooling	Single-cylinder, air-cooled
Motor Power	13
Way of Working	Recoil / Electric Start
Fuel Type	Euro Diesel
Fuel Tank Capacity	12.5 L
Fuel Consumption	2 Litre per Hour
Crankcase Oil Capacity (Lt)	1.65 L
Oily Type	15W40
Sound Level	77 A-weighted Decibel
Weight	124 kg
Dimensions	700x510x620

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

0850 222 86 28 | info@fulljenerator.com | full jenerator | full_jenerator | /fullgenerator
www.fulljenerator.com