FDK-10000SC3

Portable Generators

GENERAL SPECIFICATIONS

Engine Model	195F
Standby (kVA)	9.4 kVA
Standby (kW)	7.5 kW
Prime (kVA)	6.8 / 8.5 kVA
Continuous Output Current (Ampere)	12.2

1 Standby power: Used as a backup to mains power, as an emergency power source under variable load, no overloading.
2 Prime Power: Continuous power source under variable load for 24/24 hours. 1/12 hour 10% overloading is permitted.

TECHNICAL SPECIFICATIONS

Maximum Power (kW/kVA)	7.5 / 9.4
Continuous Power (kW/kVA)	6.8 / 8.5
Number of phases	3 (Three-phase)
Output Voltage	230 / 400 Volt
Frequency	50 Hertz
Display	Digital
Cylinders / Cooling	Single-cylinder, air-cooled
Motor Power	13
Way of Working	With a starter motor
Fuel Type	Euro Diesel
Fuel Tank Capacity	30 L
Fuel Consumption	2 Litre per Hour
Crankcase Oil Capacity (Lt)	1.65 L
Oily Type	15W40
Sound Level	72 A-weighted Decibel
Weight	192 kg
Dimensions	850x550x720

Topçular Endüstriyel Üretim ve Yatırım A.Ş. reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice.

0850 222 86 28 | info@fulljenerator.com | full jenerator | full_jenerator | /fullgenerator
www.fulljenerator.com